



SeamSAFE™

Roof Safety Anchors + Brackets

www.seamsafe.com

SUPERIOR FALL PROTECTION & VERSATILITY

BACKGROUND

The SeamSAFE anchor is the original standing seam metal roof anchor (U.S. Patent #7240770, filed November 2004). It is manufactured in the USA.

The anchor was created by Doug Mullins, owner of Construction Specialty Anchors, LLC, who has more than 40 years in the roofing industry. After a life-threatening roofing fall, Mr. Mullins invented the anchor to set a new standard for fall-arrest protection for standing seam metal roofers.



Today, SeamSAFE anchors and brackets are used throughout the country and internationally by roofing companies, contractors, and even NASA.

SEAMSAFE FEATURES and DISTINCTIONS

No other fall-arrest anchor for standing seam metal roofers matches the engineering integrity and fall-protection features provided by SeamSAFE.

SeamSAFE anchors have been independently lab tested, as well as field tested by roofers. The anchors support up to 10,500 pounds with required deflection limits, and exceed or meet OSHA: 29 CFR-1926 Subpart M and ANSI: Z359-2007 standards.

Unmatched Holding Surface: SeamSAFE anchors lead the industry in holding power. Roofers benefit from 12 inches of gripping surface, compared to only 4 or 6 inches that other anchors provide.

Extraordinary Features: Single-wrench installation in under a minute using just three bolts makes SeamSAFE attachment easier and faster than other anchors. The lightweight anchors can be transported hands free by being clipped to the roofer's belt.


Complete Safety System: SeamSAFE anchors can be paired with versatile SeamSAFE roof brackets to provide a complete system of secure support for standing seam roofers, their tools and materials.

Multi-Purpose Utility: SeamSAFE anchors are designed for temporary and permanent use. In addition to fall protection, they can be used to mount solar panels, roof jacks, and other rooftop apparatus.


SPECIFICATIONS

SeamSAFE anchors consist of two aluminum blocks that clamp on a single standing seam of a metal roof. The blocks are connected by three bolts that have washers, nuts, and locking nuts. The anchor functions by separating the blocks, fitting them over the standing seam, and then tightening the bolts with a box-end wrench.

Once a SeamSAFE anchor is properly attached to a metal roof seam and tethered to the roofer's belt or harness, the anchor will break any fall.



**Protecting Roofers Across the U.S.*
in 42 states and growing!**



■ SeamSAFE Anchors in use

**SeamSAFE Anchors can also be found in use in South Africa and Canada.*

855-263-1521 | www.seamsafe.com

SeamSAFE anchors are 12 inches long, 3 - 4 inches tall, and 2 - 2.5 inches wide, and weight 6.75 - 8 pounds, depending on the model.

Anchors are manufactured with 6061-T aircraft aluminum blocks, 1/2-inch, grade-8 shank bolts, and a 1/4-inch, solid, stainless-steel attachment ring that can be used with any tethering device and harness on the market.

When Safety Counts
COMPARE STANDING SEAM ROOF ANCHORS

	SeamSAFE Anchors	Competitor A	Competitor B
Length of Holding Surface Grip	12"	4-6"	6"
Fast Single-Wrench Installation	✓	✓	X
Number of Bolts for Easy Installation	3	12	4
Supported Weight	10,500 lbs	5,000 lbs	5,000 lbs
Aircraft Alloy Aluminum	✓	✓	X

ANCHOR MODELS

Multiple anchor sizes are available to accommodate nearly every standing seam metal roof.

Anchor Model 1 - Retail Price: \$249
Accommodates seam heights of 1.25 inches or greater and a maximum seam width of .6 inch.

Anchor Model 2 - Retail Price: \$279
Accommodates seam heights of 1.25 inches or greater and a maximum seam width of 1 inch.

Anchor Model 3 - Retail Price: \$279
Accommodates seam heights of 2.25 inches or greater and a maximum seam width of .6 inch.

Anchor Model 4 - Retail Price: \$279
Accommodates seam heights of 1.25 inches or greater and a maximum seam width of 1.3 inches.

Anchor Model 5 – Retail Price \$279
Accommodates seam heights of 1.25 inches or greater and a maximum seam width of .85 inch.

SEAMSAFE ROOF BRACKETS

When used with SeamSAFE anchors, SeamSAFE roof brackets provide the ultimate fall protection system. Paired together, they offer flexibility throughout a roofing project by providing secure support for standing seam roofers, their tools and roofing materials.

A minimum of two SeamSAFE brackets, along with anchors, are required for all applications. Like SeamSAFE anchors, the roof brackets come in multiple sizes. Bracket sizes need to correspond to the anchor sizes.



All brackets retail for \$220.

SEAMSAFE MOUNTING ADAPTERS

SeamSAFE Mounting Adapters can be used along with anchors to securely attach HVAC units, industrial piping, walk boards, handrail systems and other equipment to standing seam roofs. The adapter fits all anchor sizes and features a 4-inch x 4-inch mounting surface with precision-drilled holes.



Retail pricing for mounting adapters is two-tiered: \$90 each for 1-3 adapters and \$80 each for 4 or more adapters in a single purchase.

WHOLESALE/DISTRIBUTOR PRICING

Wholesalers are given a percentage discount based on the quantity of products ordered. Please contact us for details and terms.

COMPANY CONTACTS

Doug Mullins
SeamSAFE Inventor, Owner and Roofer
doug@constructionspecialtyanchors.com
540-537-4648 (mobile)

Kristi McClure
Vice President of Sales
kristi@constructionspecialtyanchors.com
540-598-8730 (mobile)